

CHISEL COMP SHIMANO



Gloss Dark Moss Green / Liquid Metal

CHISEL COMP SHIMANO	XS	S	M	L	XL
Stack (mm)	602.3	593	606	620	629
Reach (mm)	390	415	445	470	495
Lunghezza Tubo Sterzo (mm)	95	95	110	125	135
Angolo sterzo (basso) (degrees)	66.5	66.5	66.5	66.5	66.5
Altezza movimento centrale (BB basso) (mm)	226	336	336	336	336
Altezza movimento centrale (BB alto) (mm)	332	342	342	342	342
BB Drop (BB Basso) (mm)	46	36	36	36	36
Trail (mm)	113	113	113	113	113
Lunghezza forcella (mm)	530	530	530	530	530
Offset forcella/Rake (mm)	44	44	44	44	44
Avancorsa (mm)	682	706	742	773	802
Lunghezza Batticateni (mm)	437	437	437	437	437
Interasse (mm)	1115	1141	1177	1208	1237
Altezza standover (mm)	756	777	777	787	790
Lunghezza piantone (mm)	375	392	410	450	500
Angolo Sella (degrees)	75.5	75.5	75.5	75.5	75.5
Lunghezza Tubo Orizz. virtuale (mm)	527	565	602	634	664
Lunghezza pedivella- translate here (mm)	165m	170	170	175	175
Larghezza Manubrio (mm)	760	760	760	760	760
Lunghezza Attacco man. (mm)	60	60	60	60	60
Larghezza Sella (mm)	155	155	143	143	143
Lunghezza Reggisella (mm)	357	412	412	459	459

SPECIFICHE TECNICHE	Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.
Telaio	Specialized D'Aluisio Smartweld M5 Alloy, Hydroformed tubes, Progressive XC Geometry, 110mm travel, internal cable routing, BSA BB, 12x148mm spacing, 30.9mm Dropper post compatible
Ammortizzatore Post.	RockShox Deluxe Select+, Ride Dynamics Tuned, Two Position, Rebound Adjust, 190x40mm
Forcella	RockShox SID, Rush damper, 44mm offset, 15x110mm thru-axle, 120mm of travel, Maxle Stealth
Attacco Manubrio	Specialized, 3D-forged alloy, 4-bolt, 7-degree rise
Manopole	Specialized Trail Grips
Manubrio	Specialized Alloy, 20mm rise, 31.8mm, 760mm wide
Freno anteriore	Shimano M6100, 2-piston caliper, hydraulic disc, 180mm rotor
Freno posteriore	Shimano M6100, 2-piston caliper, hydraulic disc, 160mm rotor
Comandi cambio	Shimano SLX, M7100, 12spd
Pacco Pignoni	Shimano Deore M6100, 12spd w/Hyperglide+, 10-51t
Cambio posteriore	Shimano SLX M7100, SGS, 12-speed
Catena	Shimano Deore M6100, 12spd w/quick link
Guarnitura	Shimano MT-511, 32t chainring
Ingranaggi	32t
Movimento Centrale	Shimano BB-MT501 BSA
Cerchi	Specialized Alloy, Tubeless ready, 27mm inner width, disc, 28h
Mozzo anteriore	Shimano MT410-B, Centerlock 28h, 15x110 Boost
Mozzo posteriore	Shimano MT410-B, Centerlock 28h, 12x148 Boost, Microspline
Pneumatico anteriore	Specialized Ground Control, Control Casing, T5 Compound, 29x2.35
Pneumatico posteriore	Specialized Fast Trak, Control Casing, T5 Compound, 29x2.35
Raggi	Stainless, 14g
Camere d'aria	Standard 40mm PV 29x1.75-2.4
Sella	Body Geometry Power Sport, steel rails
Reggisella	TranzX Dropper post, 30.9mm, XS-SM: 100mm, M: 125mm, L-XL: 150mm
Collarino Sella	Specialized Alloy, 34.9mm
Peso	12.86kg (28 lb, 5.6 oz)
Misura pesata	MD

ART. NR.	DESCRIZIONE	COLORE	MISURA
93825-5101	CHISEL COMP SHIMANO	Gloss Dark Moss Green/Liquid	XS
93825-5102			S
93825-5103			M
93825-5104			L
93825-5105			XL

Disponibile Online e Pickup in store



Gloss Sea Foam / Deep Orange

CHISEL SHIMANO	XS	S	M	L	XL
Stack (mm)	602.3	593	606	620	629
Reach (mm)	390	415	445	470	495
Lunghezza Tubo Sterzo (mm)	95	95	110	125	135
Angolo sterzo (basso) (degrees)	66.5	66.5	66.5	66.5	66.5
Altezza movimento centrale (BB basso) (mm)	326	336	336	336	336
Altezza movimento centrale (BB alto) (mm)	332	342	342	342	342
BB Drop (BB Basso) (mm)	46	36	36	36	36
Trail (mm)	113	113	113	113	113
Lunghezza forcella (mm)	530	530	530	530	530
Offset forcella/Rake (mm)	44	44	44	44	44
Avancorsa (mm)	682	706	742	773	802
Lunghezza Batticatena (mm)	437	437	437	437	437
Interasse (mm)	1115	1141	1177	1208	1237
Altezza standover (mm)	756	777	777	787	790
Lunghezza piantone (mm)	375	392	410	450	500
Angolo Sella (degrees)	75.5	75.5	75.5	75.5	75.5
Lunghezza Tubo Orizz. virtuale (mm)	527	565	602	634	664
Lunghezza pedivella- translate here (mm)	165	170	170	175	175
Larghezza Manubrio (mm)	760	760	760	760	760
Lunghezza Attacco man. (mm)	60	60	60	60	60
Larghezza Sella (mm)	155	155	143	143	143
Lunghezza Reggisella (mm)	357	412	412	459	459

SPECIFICHE TECNICHE	Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.
Telaio	Specialized D'Aluisio Smartweld M5 Alloy, Hydroformed tubes, Progressive XC Geometry, 110mm travel, internal cable routing, BSA BB, 12x148mm spacing, 30.9mm Dropper post compatible
Ammortizzatore Post.	X-Fusion PRO-02, 190x40mm, Ride Dynamics Tuned, Rebound adjust, Compression Adjust
Forcella	Rockshox Recon Silver RL, 120mm travel, Motion Control damper, 42mm offset, Maxle Stealth, 15x110 thru-axle
Attacco Manubrio	Specialized, 3D-forged alloy, 4-bolt, 7-degree rise
Manopole	Specialized Trail Grips
Manubrio	Specialized Alloy, 20mm rise, 31.8mm, 760mm wide
Freno anteriore	Shimano M4100, 2-piston caliper, hydraulic disc, 180mm rotor
Freno posteriore	Shimano M4100, 2-piston caliper, hydraulic disc, 160mm rotor
Cambio posteriore	Shimano Deore, M6100, 12pd, Shadow Plus
Comandi cambio	Shimano Deore, M6100, I-Spec EV, 12 speed
Pacco Pignoni	Shimano Deore M6100, 12spd w/Hyperglide+, 10-51t
Catena	KMC X12EPT, 12-speed, anti-corrosion coating w/ reusable Missing Link™
Ingranaggi	32t
Guarnitura	Alloy crankset, 1x direct mount chainring, 165/170/175mm
Movimento Centrale	BSA Bottom Bracket, PW-MBB73
Cerchi	Specialized Alloy, Tubeless ready, 27mm inner width, disc, 28h
Mozzo anteriore	Shimano MT410-B, Centerlock 28h, 15x110 Boost
Mozzo posteriore	Shimano MT410-B, Centerlock 28h, 12x148 Boost, Microspline
Pneumatico anteriore	Specialized Ground Control, Control Casing, T5 Compound, 29x2.35
Pneumatico posteriore	Specialized Fast Trak, Control Casing, T5 Compound, 29x2.35
Raggi	Stainless, 14g
Camere d'aria	Standard 40mm PV 29x1.75-2.4
Sella	Body Geometry Power Sport, steel rails
Reggisella	TranzX Dropper, 30.9mm, XS-SM: 100mm, M: 125mm, L-XL: 150mm
Collarino Sella	Specialized Alloy, 34.9mm
Peso	13.73kg (30 lb, 4.3 oz)
Misura pesata	MD

ART. NR.	DESCRIZIONE	COLORE	MISURA
93825-5001	CHISEL BASE SHIMANO	Gloss Sea Foam / Deep Orange	XS
93825-5002			S
93825-5003			M
93825-5004			L
93825-5005			XL

Disponibile Online e Pickup in store



Gloss Ion/ Smoke Liquid Metal



Satin Metallic Deep Lake / Glo

CHISEL COMP	XS	S	M	L	XL
Stack (mm)	602.3	593	606	620	629
Reach (mm)	390	415	445	470	495
Lunghezza Tubo Sterzo (mm)	95	95	110	125	135
Angolo sterzo (basso) (degrees)	66.5	66.5	66.5	66.5	66.5
Altezza movimento centrale (BB basso) (mm)	326	336	336	336	336
Altezza movimento centrale (BB alto) (mm)	332	342	342	342	342
BB Drop (BB Basso) (mm)	46	36	36	36	36
Trail (mm)	113	113	113	113	113
Lunghezza forcella (mm)	530	530	530	530	530
Offset forcella/Rake (mm)	44	44	44	44	44
Avancorsa (mm)	682	706	742	773	802
Lunghezza Batticateni (mm)	437	437	437	437	437
Interasse (mm)	1115	1141	1177	1208	1237
Altezza standover (mm)	756	777	777	787	790
Lunghezza piantone (mm)	375	392	410	450	500
Angolo Sella (degrees)	75.5	75.5	75.5	75.5	75.5
Lunghezza Tubo Orizz. virtuale (mm)	527	565	602	634	664
Lunghezza pedivella- translate here (mm)	165	170	170	175	175
Larghezza Manubrio (mm)	760	760	760	760	760
Lunghezza Attacco man. (mm)	60	60	60	60	60
Larghezza Sella (mm)	155	155	143	143	143
Lunghezza Reggisella (mm)	357	412	412	459	459

SPECIFICHE TECNICHE

Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.

Telaio	Specialized D'Aluisio Smartweld M5 Alloy, Hydroformed tubes, Progressive XC Geometry, 110mm travel, internal cable routing, BSA BB, 12x148mm spacing, 30.9mm Dropper post compatible
Ammortizzatore Post.	RockShox Deluxe Select+, Ride Dynamics Tuned, Two Position, Rebound Adjust, 190x40mm
Forcella	RockShox SID, Rush damper, 44mm offset, 15x110mm thru-axle, 120mm of travel, Maxle Stealth
Attacco Manubrio	Specialized, 3D-forged alloy, 4-bolt, 7-degree rise
Manopole	Specialized Trail Grips
Manubrio	Specialized Alloy, 20mm rise, 31.8mm, 760mm wide
Freno anteriore	SRAM Level T hydraulic disc, 2-Piston Caliper, 180mm rotor
Freno posteriore	SRAM Level T hydraulic disc, 2-Piston Caliper, 160mm rotor
Cambio posteriore	SRAM GX Eagle, 12-speed
Comandi cambio	SRAM GX, trigger, 12-speed
Pacco Pignoni	SRAM PG-1230 EAGLE 11-50t
Catena	SRAM SX Eagle, 12-speed
Guarnitura	SRAM X1000 Eagle, DUB, 165/170/175mm 32T
Ingranaggi	Steel, 30T
Movimento Centrale	SRAM DUB, BSA 73mm, Threaded
Cerchi	Specialized Alloy, Tubeless ready, 27mm inner width, disc, 28h
Mozzo anteriore	Specialized alloy front hub, disc, sealed cartridge bearings, 6-bolt, 15x110mm thru-axle, 28h
Mozzo posteriore	Specialized alloy, disc, sealed cartridge bearings, 6-bolt, 12x148mm thru-axle, 28h
Pneumatico posteriore	Specialized Fast Trak, Control Casing, T5 Compound, 29x2.35
Pneumatico anteriore	Specialized Ground Control, Control Casing, T5 Compound, 29x2.35
Raggi	Stainless, 14g
Camere d'aria	Standard 40mm PV 29x1.75-2.4
Sella	Body Geometry Power Sport, steel rails
Reggisella	TranzX Dropper, 30.9mm, XS-SM: 100mm, M: 125mm, L-XL: 150mm
Collarino Sella	Specialized Alloy, 34.9mm

ART. NR.	DESCRIZIONE	COLORE	MISURA
93825-5201/5	CHISEL COMP	Gloss Ion/ Smoke Liquid Metal	XS/XL
93825-5301	CHISEL COMP	Satin Metallic Deep Lake / Glo	XS
93825-5302/5			S/XL

Disponibile Online e Pickup in store



Gloss Dove Grey / Ashen Grey



Gloss Maroon / White

CHISEL	XS	S	M	L	XL
Stack (mm)	602.3	593	606	620	629
Reach (mm)	390	415	445	470	495
Lunghezza Tubo Sterzo (mm)	95	95	110	125	135
Angolo sterzo (basso) (degrees)	66.5	66.5	66.5	66.5	66.5
Altezza movimento centrale (BB basso) (mm)	26	336	336	336	336
Altezza movimento centrale (BB alto) (mm)	332	342	342	342	342
BB Drop (BB Basso) (mm)	46	36	36	36	36
Trail (mm)	113	113	113	113	113
Lunghezza forcella (mm)	530	530	530	530	530
Offset forcella/Rake (mm)	44	44	44	44	44
Avancorsa (mm)	682	706	742	773	802
Lunghezza Batticatena (mm)	437	437	437	437	437
Interasse (mm)	1115	1141	1177	1208	1237
Altezza standover (mm)	756	777	777	787	790
Lunghezza piantone (mm)	375	392	410	450	500
Angolo Sella (degrees)	75.5	75.5	75.5	75.5	75.5
Lunghezza Tubo Orizz. virtuale (mm)	527	565	602	634	664
Lunghezza pedivella- translate here (mm)	165	170	170	175	175
Larghezza Manubrio (mm)	760	760	760	760	760
Lunghezza Attacco man. (mm)	60	60	60	60	60
Larghezza Sella (mm)	155	155	143	143	143
Lunghezza Reggisella (mm)	357	412	412	459	459

SPECIFICHE TECNICHE	Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.
Telaio	Specialized D'Aluisio Smartweld M5 Alloy, Hydroformed tubes, Progressive XC Geometry, 110mm travel, internal cable routing, BSA BB, 12x148mm spacing, 30.9mm Dropper post compatible
Ammortizzatore Post.	X-Fusion PRO-02, 190x40mm, Ride Dynamics Tuned, Rebound adjust, Compression Adjust
Forcella	Rockshox Recon Silver RL, 120mm travel, Motion Control damper, 42mm offset, Maxle Stealth, 15x110 thru-axle
Attacco Manubrio	Specialized, 3D-forged alloy, 4-bolt, 7-degree rise
Manopole	Specialized Trail Grips
Manubrio	Specialized Alloy, 20mm rise, 31.8mm, 760mm wide
Freno anteriore	SRAM Level T hydraulic disc, 2-Piston Caliper, 180mm rotor
Freno posteriore	SRAM Level T hydraulic disc, 2-Piston Caliper, 160mm rotor
Cambio posteriore	SRAM NX Eagle, 12-speed
Comandi cambio	SRAM SX Eagle, trigger, 12-speed
Pacco Pignoni	SRAM PG-1210 Eagle 11-50t
Catena	SRAM SX Eagle, 12-speed
Guarnitura	SRAM SX Eagle, Powerspline, 32t chainring, 165/170/175mm
Ingranaggi	32t
Movimento Centrale	SRAM Powerspline BSA
Cerchi	Specialized Alloy, Tubeless ready, 27mm inner width, disc, 28h
Mozzo anteriore	Specialized alloy front hub, disc, sealed cartridge bearings, 6-bolt, 15x110mm thru-axle, 28h
Mozzo posteriore	Specialized alloy, disc, sealed cartridge bearings, 6-bolt, 12x148mm thru-axle, 28h
Pneumatico anteriore	Specialized Ground Control, Control Casing, T5 Compound, 29x2.35
Pneumatico posteriore	Specialized Fast Trak, Control Casing, T5 Compound, 29x2.35
Raggi	Stainless, 14g
Camere d'aria	Standard 40mm PV 29x1.75-2.4
Sella	Body Geometry Power Sport, steel rails, 143/155mm
Reggisella	TranzX Dropper Seatpost, 30.9mm, XS-SM: 100mm, M: 125mm, L-XL: 150mm
Collarino Sella	Specialized Alloy, 34.9mm
Peso	13.87kg (30 lb, 9.2 oz)
Misura pesata	MD

ART. NR.	DESCRIZIONE	COLORE	MISURA
93825-7001	CHISEL	Gloss Dove Grey / Ashen Grey	XS
93825-7002/5	CHISEL		S - XL
93825-7101/5	CHISEL	Gloss Maroon / White	XS - XL

Disponibile Online e Pickup in store

TELAIO CHISEL



Gloss Rebel Pink Tint Organic Brushed / Satin Ion Metallic

SPECIFICHE TECNICHE	Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.
Telaio	Specialized D'Aluisio Smartweld M5 Alloy, Hydroformed tubes, Progressive XC Geometry, 110mm travel, internal cable routing, BSA BB, 12x148mm spacing, 30.9mm Dropper post compatible
Ammortizzatore Post.	RockShox Deluxe Select+, Ride Dynamics Tuned, Two Position, Rebound Adjust, 190x40mm
Collarino Sella	Specialized Alloy, 34.9mm
Peso	2.72kg (5 lb, 15.9 oz)
Misura pesata	MD

TELAIO CHISEL	XS	S	M	L	XL
Stack (mm)	602.3	593	606	620	629
Reach (mm)	390	415	445	470	495
Lunghezza Tubo Sterzo (mm)	95	95	110	125	135
Angolo sterzo (basso) (degrees)	66.5	66.5	66.5	66.5	66.5
Altezza movimento centrale (BB basso) (mm)	326	336	336	336	336
Altezza movimento centrale (BB alto) (mm)	332	342	342	342	342
BB Drop (BB Basso) (mm)	46	36	36	36	36
Trail (mm)	113	113	113	113	113
Lunghezza forcella (mm)	530	530	530	530	530
Offset forcella/Rake (mm)	44	44	44	44	44
Avancorsa (mm)	682	706	742	773	802
Lunghezza Batticateni (mm)	437	437	437	437	437
Interasse (mm)	1115	1141	1177	1208	1237
Altezza standover (mm)	756	777	777	787	790
Lunghezza piantone (mm)	375	392	410	450	500
Angolo Sella (degrees)	75.5	75.5	75.5	75.5	75.5
Lunghezza Tubo Orizz. virtuale (mm)	527	565	602	634	664

ART. NR.	DESCRIZIONE	COLORE	MISURA
73825-7001/5	CHISEL FRM	Gloss Rebel Pink Tint Organic	XS - XL

Disponibile Online e Pickup in store