

S-WORKS EPIC WORLD CUP FORWARD 50 LTD



FORWARD 50

S-WORKS EPIC WORLD CUP FORWARD 50 LTD

	S	M	L	XL
Stack (mm)	600	600	614	628
Reach (mm)	415	440	465	490
Lunghezza Tubo Sterzo (mm)	93	95	110	125
Angolo sterzo (degrees)	66.5	66.5	66.5	66.5
Altezza movimento centrale (mm)	313	313	313	313
BB Drop (mm)	58	57	57	57
Trail (mm)	113	113	113	113
Lunghezza forcella (mm)	516	516	516	516
Offset forcella/Rake (mm)	44	44	44	44
Avancorsa (mm)	701	726	757	788
Lunghezza Batticateni (mm)	430	430	430	430
Interasse (mm)	1124	1150	1181	1212
Altezza Standover (mm)	761	764	774	786
Lunghezza piantone (mm)	395	410	450	500
Angolo Sella (degrees)	74.5	74.5	74.5	74.5
Lunghezza Tubo Orizz. virtuale (mm)	581	612	641	670
Lunghezza pedivella (mm)	170	170	175	175
Larghezza Manubrio (mm)	760	760	760	760
Lunghezza Attacco man. (mm)	60	70	70	70
Larghezza Sella (mm)	155	143	143	143
Lunghezza Reggisella (mm)	370	415	415	415

SPECIFICHE TECNICHE

Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.

Telaio	S-Works FACT 12m Carbon, WCID suspension design, Progressive XC Race Geometry, Rider-First Engineered™, threaded BB, 12x148mm UDH compatible rear spacing, internal cable routing, 75mm of travel
Componenti SWAT	SWAT EMT Cage-Mount Tool
Ammortizzatore Post.	RockShox-Specialized SID Luxe WCID Ultimate, Ride Dynamics Developed, Independent negative spring, Rebound Adjust, 215x40mm
Forcella	RockShox SID SL Ultimate, 3-position Raceday damper, Debon Air, 15x110mm, 44mm offset, 110mm Travel
Manubrio	Royal Control SL Integrated cockpit, 60mm/70mm X- 12 degree integrated stem, 8-degree backsweep, 1 degree upsweep, 760mm wide
Manopole	SRAM Twist Loc
Freno anteriore	SRAM Level Ultimate, 4-piston caliper, hydraulic disc, stealth, 180/160mm rotor
Freno posteriore	SRAM Level Ultimate, 4-piston caliper, hydraulic disc, stealth, 160mm rotor
Cambio posteriore	SRAM XX SL Eagle Transmission
Comandi cambio	SRAM POD Ultimate AXS controller
Pacco Pignoni	SRAM CS-1299 10-52t
Catena	SRAM XX Eagle
Guarnitura	Quarq XX SL power meter crankset, Carbon, 168 Q-Factor, DUB, 170/175mm, 34T
Ingranaggi	34t
Movimento Centrale	Ceramicspeed DUB BSA 73mm
Cerchi	Control SL 29, 4mm FlatTop Bead Hooks, 29mm internal width, Tubeless Compatible, Tire Insert Compatible, 20h
Mozzo anteriore	Royal Control SL Team, DT Swiss Internals, Ceramic Bearings, 6-bolt, 15mm thru-axle, 110mm spacing, Torque caps, 20h
Mozzo posteriore	Royal Control SL, DT Swiss 180 Internals, DT Swiss Ratchet EXP, Ceramic bearings, 12mm thru-axle, 148mm spacing, 20h
Raggi	Royal by VONOA Carbon Round Straightpull
Pneumatico anteriore	Specialized Fast Trak, S-Works Casing, T5/T7 Compound, 29x2.35
Pneumatico anteriore	Specialized S-Works Fast Trak, S-Works Casing, T5/T7 Compound, 29x2.35
Pneumatico posteriore	Specialized Renegade, S-Works Casing, T5/T7 Compound, 29x2.35
Camere d'aria	Specialized Turbo Tube
Sella	Body Geometry S-Works Power Mirror, carbon fiber rails, carbon fiber base, 143mm/155mm
Reggisella	Royal Control SL carbon seatpost, T two-bolt clamp, 0mm offset, 415/370mm x 30.9
Collarino Sella	Specialized Alloy 34.9, Titanium Bolt
Peso	221793
Peso	9.31kg (20 lb, 8.4 oz)
Misura pesata	MD

ART. NR.	DESCRIZIONE	COLORE	MISURA
93125-0402	SW EPIC WC FORWARD 50 LTD	FORWARD 50	S
93125-0403			M
93125-0404			L
93125-0405			XL

Disponibile Online e Pickup in store